

### Product Information

**Construction** - Heterogeneous

**International Specifications** - ASTM F1303, Type I, Grade 1, Class B

**Overall Thickness** - 0.080 in. (2.0 mm)


**Wear Layer Thickness** - 0.022 in. (0.55 mm)

**Factory Finish** - UV-cured Polyurethane

**Installation** - Full Spread Adhesive: S-995 Adhesive, S-580 Flash Cove Adhesive

Seams - Heat Weld or S-761 Seam Adhesive

**Maintenance Options** - Polish, No Polish - No Buff, No Polish - Spray Buff



### Packaging

#### Roll Length

Up to 82 ft. (25 m)

#### Roll Width

6 ft. (1.83 m)

#### Shipping Weight per Carton

6.08 lbs./sq. yd (3.3 kg/m<sup>2</sup>)

### Testing

| ASTM F1303                                      |                           |   |  |
|---|---------------------------|---|--|
| Performance                                     | Test Method               | Requirement   | Performance vs. Requirement            |
| Wear Layer Composition                          | Certificate of Compliance | 90% binder  | Meets                                  |
| Wear Layer Thickness                            | ASTM F410                 | ≥ 0.020 in.   | Meets                                  |
| Total Thickness                                 | ASTM F386                 | ≥ 0.040 in.   | Meets                                  |
| Residual Indentation                            | ASTM F1914                | ≤ 0.012 in.   | Meets                                  |
| Static Load Resistance @ 175 psi                | ASTM F970                 | ≤ 0.005 in.   | Meets                                  |
| Flexibility                                     | ASTM F137                 | 1/4" mandrel no cracks or breaks in wear surface                  | Meets                                  |
| Resistance to Chemicals                         | ASTM F925                 | No more than slight change in surface dulling, attack or staining | Meets                                  |
| Resistance to Heat                              | ASTM F1514                | ΔE ≤ 8  | Meets                                  |
| Resistance Light                                | ASTM F1515                | ΔE ≤ 8  | Meets                                  |
| Additional Testing                              |                           |   |  |
| Fire Test Data – Flame Spread                   | ASTM E648                 | 0.45 W/cm <sup>2</sup> or more Class 1                            | Meets                                  |
| Fire Test Data – Smoke Evolution                | ASTM E662                 | 450 or less   | Meets                                  |
| Fire Test Data – Canada                         | CAN\ULC S-102.2           | Use dependent   | Flame Spread - 15 Smoke Developed - 95 |
| Static Load Resistance                          | ASTM F970*                | < 0.005 in.   | 750 psi (52.73 kg/cm <sup>2</sup> )    |
| Wear Group Classification per EN649-volume loss | EN660-2                   | -   | Wear Group T ≤ 2.0 mm <sup>3</sup>     |
| ADA Standards for Accessible Design             | CHAPTER 3 SECTION 302.1   | Floor surfaces shall be stable, firm and slip-resistant           | Meets                                  |
| Static Coefficient of Friction**                | ASTM D2047/UL 410         | ≥ 0.5 in.   | Meets                                  |

### Sustainability

| WELL v1 Feature |   | Rejuvenations Classics | Contribution   |
|-----------------|---|------------------------|--|
| Air             | Feature 04 - VOC Reduction                    | ✓                      | Tested and third party certified by FloorScore® as complying with CDPH v1.2        |
|                 | Feature 11 - Fundamental Material Safety      | ✓                      | Product is free of asbestos and added lead (Part 1)                                |
|                 | Feature 25 - Toxic Material Reduction         | ✓                      | Free of flame retardants (Part 2) and phthalates (Part 3)                          |
| Mind            | Feature 97 - Material Transparency            | ✓                      | Readily available Health Product Declaration® (HPD) to 1000 ppm                    |
|                 | Feature 88 (Part 2) Biophilia I - Qualitative | ✓                      | Products available that incorporate nature patterns                                |
|                 | Feature 99 - Beauty and Design II             | ✓                      | Provided patterns and colors to aid in wayfinding and spatial familiarity (Part 3) |

| WELL v2 Feature   |   | Rejuvenations Classics            | Contribution   |
|---|---|-----------------------------------|--|
| Materials   | Feature X01.1<br>Material Restrictions          | ✓                                 | Product is free of asbestos  |
|   | Feature X05.1<br>Enhanced Material Restrictions | ✓                                 | Free of flame retardants (Part 2) and phthalates (Part 3)  |
|   | Feature X06.1<br>VOC Restrictions               | ✓                                 | Adhesives associated with product are tested and third party certified by FloorScore as complying with CDPH v1.2 |
|   | Feature X06.2<br>VOC Restrictions               | ✓                                 | Flooring is tested and third party certified by FloorScore as complying with CDPH v1.2                           |
|   | Feature X07.1<br>Material Transparency          | ✓                                 | Readily available Health Product Declaration (HPD) to 1000 ppm   |
|   | Mind  | Feature M02.1<br>Nature and Place | ✓  |
| Community<br>Feature C13 (Part 2)<br>Accessibility and Universal Design |   | ✓                                 | Provided patterns and colors to aid in wayfinding and spatial familiarity  |

| LEED™ v4.1                          | Rejuvenations Classics  |
|-------------------------------------|---|
| BPDO - EPD                          | Product Specific  |
| BPDO - Material Ingredient          | HPD   |
| BPDO - Sourcing                     | EPR - On&On Recycling Program   |
| Location of Manufacturer            | Korea   |
| Low Emitting Flooring               | Tested and third party certified by FloorScore as complying with CDPH v1.2  |
| Low Emitting Adhesives              | Tested and compliant to CDPH v1.2; Methylene Chloride and Perchloroethylene not intentionally added; FloorScore Certified |
| SCAQMD #1168 Compliant.             | S-995 – 0 g/L   |
| Adhesives meet <50 g/L requirement. | S-580 – 0 g/L   |

| Carbon Footprint   | Rejuvenations Classics  |
|--|---|
| Global Warming Potential, including Biogenic Carbon Raw Materials (A1) through Production (A3) | 0.91 kg CO <sup>2</sup> eq. / square foot<br>(9.78 kg CO <sup>2</sup> eq. / square meter) |

### Limited Warranty

10-year Commercial Warranty when installed in strict accordance with the detailed instructions.

### Visit ArmstrongFlooring.com

for complete Product, Technical, Adhesives, Installation & Maintenance recommendations.

#### F10163-122

Armstrong and the Armstrong logo are under license from AWI Licensing LLC. | All other trademarks are owned by AFI Licensing LLC. | © 2022 AFI Licensing LLC. FloorScore® is a registered trademark of the Resilient Floor Covering Institute. | LEED® is a registered trademark of the United States Green Building Council. The Health Product Declaration® logo is a registered trademark of HPD Collaborative.

\*Testing at loads above 250 psi is outside the scope of the test method. Since testing is conducted on uninstalled flooring, results do not consider the performance of the adhesive, underlayment, or subfloor. These test results are not an indicator of the installed flooring system performance.\*\* Using the James Machine as described in D2047 and as directed in UL 410 for floor covering materials (FCM) using a leather foot under dry conditions. The application of site-applied floor sealers, polishes and other types of finishes routinely used to maintain resilient flooring materials will change the walking surface and consequently the SCOF value.

