

# S-725 Wall Base Adhesive



**CAUTION**

S-725 **EYE AND SKIN IRRITANT**

---

## STIR WELL BEFORE USING.

For use with the following Installation System:

- Wall Base, Risers, and Vinyl Transition Strips

---

## DESCRIPTION:

<b>Type:</b>	Water-based/rubber-resin
<b>Color:</b>	Off-white
<b>Taggants:</b>	Yes — 50% yellow and 50% orange
<b>Trowel:</b>	1/16" deep, 1/16" wide, 3/32" apart), U-notch
<b>Coverage:</b>	2-1/2" Wall Base: 375–425 lin. ft./gal (114–130 m lin.) 4" Wall Base: 300–350 lin. ft./gal (91–107 m lin.) 6" Wall Base: 200–250 lin. ft./gal (61–76 m lin.) 7" RISER: 200–250 lin. ft./gal (61–76 m lin.) 11-oz. cartridge — 4": 1/8" bead — 18 lin. ft. (5.5 m lin.) 30-oz. cartridge — 4": 1/8" bead — 50 lin. ft. (15.2 m lin.)
<b>Units:</b>	11-oz. cartridge (311.8 grams) 30-oz. cartridge (950.4 grams) quart (946 ml) gallon (3.78 L) 4 gallons (15.14 L)
<b>Open Time:</b>	None recommended
<b>Working Time:</b>	Up to 15 minutes
<b>Shelf Life:</b>	1 year, unopened
<b>Freeze/Thaw Stable:</b>	Yes, to 10° F (-12° C)
<b>VOC Content:</b>	Zero g/L; calculated and reported, SCAQMD 1168
<b>Clean Up:</b>	Wet — clean, white cloth with neutral detergent and water Dry — clean, white cloth and mineral spirits
<b>Walls:</b>	Structurally sound and dry wall surfaces
<b>Advantages:</b>	Moisture and alkali resistant Good wet strength Excellent bond integrity Versatile (use for rubber or vinyl Wall Base) AGIS Guarantee Nonflammable