



Armstrong®  
FLOORING



ELECTROSTATIC DISSIPATIVE

EXCELON®

SDT™



# Control Static, Provide Peace of Mind

Excelon® SDT™ static dissipative tile is designed to control static in most non-explosive manufacturing and working areas. The exclusive four-part system works together to dissipate electrostatic charges, protecting people and preventing damage to expensive equipment.

Excelon SDT is recommended for computer training rooms, data warehousing, electronic testing labs, manufacturing facilities, and hyperbaric spaces in healthcare settings. Its durable and versatile construction ensures lasting beauty in high-traffic areas and it's easy to maintain using standard maintenance protocols.



## Exclusive ESD Formulation with Fast Start Factory Finish

- Protection against electrostatic discharge
- Makes initial maintenance quick and easy

## True Through-Pattern Wear Layer

- Pattern/color wear performance:
  - High durability
  - Gouge resistance
  - Rolling load impact resistance\*
  - Appearance retention

\*Visit [ArmstrongFlooring.com](http://ArmstrongFlooring.com) for complete installation, care and maintenance information.



# An Exclusive Four-Part System

Only Armstrong Flooring fulfills your specialized requirements from installation through maintenance with an exclusive four-part system. Tile, adhesive, copper grounding strips, and polish work together to create a continuous static dissipative surface, keeping occupants and equipment safe.

## 1. Excelon SDT Tile

- Available in eight on-trend colors in 12 in. x 12 in. tiles
- Works in harmony with other products across the Armstrong Flooring portfolio giving you the design flexibility you need to create a beautiful, coordinated space

## 2. S-202 SDT Adhesive

- Excellent bond strength

## 3. Copper Grounding Strips

- An integral element to prevent electrostatic discharge and supplied with the S-202 SDT Adhesive

## 4. S-392 Static Dissipative Polish

- Specifically formulated to enhance the appearance of Excelon SDT while maintaining proper electrical characteristics
- Meets the ASTM D 2047 Standard for slip-resistance on dry floors
- Dries bright for areas where buffing is not applicable or desired




# Seamless Design & Surface Transitions

Developed as part of Continuum™ Solutions, Excelon SDT works in harmony with other products across the Armstrong Flooring portfolio so you can combine distinctive patterns, colors and textures while meeting static dissipative performance requirements. The thickness of Excelon SDT allows an easy transition to adjoining VCT, BBT or LVT resulting in a seamless, coordinated look.

## Healthy Environments


- Low VOC Emissions and FloorScore® Certified
- Recyclable through the On&On™ Recycling Program
- Third-party certified Environment Product Declaration (EPD)
- Made with Recycled Content – 30% pre consumer
- Complies with LEED® v4 Material Ingredients Reporting

51953 pearl white



12 in. x 12 in.

51950 marble beige



12 in. x 12 in.

51951 armor gray



12 in. x 12 in.

51960 beach



12 in. x 12 in.

51956 fossil gray



12 in. x 12 in.

51959 coal



12 in. x 12 in.

51957 ridge



12 in. x 12 in.

51958 ocean air



12 in. x 12 in.

51953 pearl white, 51957 ridge, 51958 ocean air  
Excelon® SDT™