70013 Waikiki

Natralis™

Homogeneous Sheet

70001 White Rim

Proven Floor for Healthy Environments

Natralis™ is more than just a beautiful flooring design. It's carefully crafted to promote wellness and inspire creativity in healthcare and education settings. The natural elements within the design create a calming and restorative environment, while the dynamic speckles stimulate the imagination. And with its durable and easy-to-clean construction, Natralis can withstand the demands of high-traffic environments.

70001 White Rim, 70017 Utah



70001 White Rim Weld Rod #WH231



70006 Birch Syrup Weld Rod #WH233



70010 Sand Dune Weld Rod #WH236



70007 Meadow Weld Rod #WE128



70008 River Rock Weld Rod #WH234



70019 Cape Pillar Weld Rod #WH214



70011 Prairie Weld Rod #WE117



70017 Utah Weld Rod #WH242



70018 Bryce Red Weld Rod #WH243

Building Better

We share your commitment to transparency and building a better environment together.

- Third-party certified Environmental Product Declaration (EPD) available
- Low VOC emissions and FloorScore® certified
- Free of Ortho-phthalates and heavy metals – meets Well Building Standard® Toxic Material Reduction Credit requirements

70021 Volcano Weld Rod #WH245



70009 Petrified Gray Weld Rod #WH235



70003 Hot Springs Weld Rod #WN112



70002 Arctic Weld Rod #WH232



70004 Spray Foam Weld Rod #WN101



70013 Waikiki Weld Rod #WH238



70012 Kenai Lagoon Weld Rod #WH237



70014 Neptune Jade Weld Rod #WH239



70005 Glacier Bay Weld Rod #WN101



70015 Nugget Falls Weld Rod #WH240

70020 Radiant Weld Rod #WH244



70022 Vanta Weld Rod #WN116



70016 Pacific Weld Rod #WH241

70001 White Rim, 70010 Sand Dune

Durable Performance

Natralis™ homogeneous vinyl sheet commercial flooring is highly durable, easy to clean, low maintenance and meets high performance criteria. Natralis has a low-maintenance polyurethane coating that eliminates the need to polish.

70004 Spray Foam, 70008 River Rock, 70012 Kenai Lagoon



1. Commercial Polyurethane Coating

2. True Through-Pattern Wear Layer

10 Year Commercial Limited Warranty

Supported by a 10 Year Commercial Warranty. Add 10 years of overall warranty coverage by using Strong System™ subfloor preparation products. Visit armstrongflooring.com for more information.

Product Information

Construction - Homogeneous Sheet
International Specifications - ASTM F1913
Overall Thickness - 0.08 in. (2.0 mm)
Wear Layer Thickness - 0.08 in. (2.0 mm)
Size - Up to 43.78 yd.² (36.61 m) 6 ft. (1.83 m)
Factory Finish - Commercial Polyurethane Coating
Installation - Full Spread Adhesive: S-995
Seams - Heat Weld or S-761 Seam Adhesive
Maintenance Options - No Polish - No Buff, Polish Optional

Shade may vary from sample.

ArmstrongFlooring™
Walk On. Walk Strong.™

Visit ArmstrongFlooring.com
for complete Product, Technical, Adhesives, Installation and Maintenance recommendations.

Print#: AF-1054-724

Armstrong and the Armstrong logo are under license from AWI Licensing LLC. | All other trademarks are owned by AHF Licensing LLC. | © 2024 AHF Licensing LLC.
FloorScore® is a registered trademark of the Resilient Floor Covering Institute. | Well Building Standard® is a registered trademark of the International Well Building Institute.™