







H2011 Ginger

# Designs Encourage Comfort, Happiness & Healing

Medintone™ is engineered for spaces demanding superior infection control, helping to protect the health and well-being of occupants in healing and learning environments.

The durability and cleanability of Medintone works in harmony with a color palette inspired by nature. From calming blues and greens, to soothing neutrals and golden tones, Medintone offers boundless opportunities for design that encourages comfort, happiness, and healing.







H2006 Calming Gray, H2027 Cedar, Natralis: 70001 White Rim

### Building Better

We share your commitment to transparency and building a better environment together.

- Low VOC emissions and FloorScore® certified
- Free of Ortho-phthalates and heavy metals
- Health Product Declaration (HPD) and third-party certified Environmental Product Declaration (EPD) available



Superior infection control with heat welded seams for spaces demanding enhanced sterilization.



Medintone™ provides pop colors to provide a playful palette that makes it easy to incorporate branding, school colors, and wayfinding elements.




# Diamond 10<sup>®</sup> Technology

Diamond 10 Technology coating provides the ultimate scratch, stain, and scuff resistance. It's a no-polish, easy-to-clean solution that is designed to look beautiful for years to come, despite daily maintenance and rigorous disinfection protocols.

- Protects against scratches, stains, and scuffs for floors that look newer, longer
- Offers ease of maintenance no polishing, stripping, or restorative maintenance required



H2025 Lavendula, H2023 Lemon Balm, H2031 Jasmine Bloom



- 1. Diamond 10® Technology
- 2. Through Pattern Wear Layer

### 10 Year Commercial **Limited Warranty**

Supported by a 10 Year Commercial Warranty. Add 10 years of overall warranty coverage by using Strong System<sup>™</sup> subfloor preparation products. Visit armstrongflooring.com for more information.

#### **Product Information**

Construction - Homogeneous Sheet

**International Specifications** - ASTM F1913

Overall Thickness - 0.080 in. (2.0 mm)

Wear Layer Thickness - 0.080 in. (2.0 mm)

**Size** - Up to 65.62 ft (20 m) 6.5 ft. (1.98 m)

Factory Finish - Diamond 10® Technology

Installation - Full Spread Adhesive: S-995

Seams: Heat Weld or S-761 Seam Adhesive

Maintenance Options - No Polish - No Buff, Polish Optional

Shade may vary from sample.



Walk On. Walk Strong.





#### Visit ArmstrongFlooring.com

for complete Product, Technical, Adhesives, Installation and Maintenance recommendations.