

Inspiring Great Spaces®

**Armstrong®**  
**FLOORING**



Natural Creations® with Diamond 10® Technology

## S-315 ROLL STRONG™ ADHESIVE FOR EASY LVT INSTALLATION

Roll Strong™ adhesive allows for installation flexibility to meet the demands of commercial and residential LVT applications. It is applied using a 3/8" nap roller instead of a trowel for a less time consuming installation.

- One coat, rolled on application provides a strong instant grab
- Two coat system for absorbent or dirty subfloors minimizes the amount of subfloor preparation
- Normal traffic and rolling loads are allowed on the floor immediately after installation is complete
- Backed by Armstrong Guaranteed Installation System warranty



## S-315 ROLL STRONG™ ADHESIVE

FOR EASY LVT INSTALLATION



### PRODUCT INFORMATION

SIZE	1 gallon or 4 gallon pail
SPREAD RATE	350-400 square feet per gallon
SUBFLOORS	All grade levels of concrete, existing resilient floors, ceramic, terrazzo, marble, polymeric poured floors and suspended wood
OPEN TIME	15 or more minutes
WORKING TIME	Up to 4 hours
APPLICATION METHOD	Adhesive is rolled on using a 3/8" nap roller
RH LIMIT	95%
USE WITH	Armstrong® Flooring Luxury Vinyl Tile
WARRANTY	Armstrong® Guaranteed Installation System