

FOR EASY LVT INSTALLATION

Roll Strong™ Adhesive provides installation flexibility for commercial and residential LVT, commercial VCT, and Armstrong Flooring Slip Retardant Flooring (Safety Zone Tile). It is applied with a 3/8-inch nap roller instead of a trowel, helping reduce installation time while delivering consistent adhesive coverage.



S-319 Roll Strong™ Adhesive

- One coat, rolled on application provides a strong instant grab.
- Normal traffic and rolling loads are allowed on the floor immediately after installation is complete.
- Shelf life 12 months unopened
- Dry-to-touch (ready to receive flooring) in mere minutes.
- Apply with roller from a standing position.
- Eliminate adhesive trowel ridge telegraphing/show through.



Size	1 Gallon or 4 Gallons
Spread Rate	1,200 - 1,600 square feet per 4 gallon
Subfloors	All grade levels of concrete, existing resilient floors, ceramic, terrazzo, marble, polymeric poured floors and suspended wood
Open Time	Dry to touch
Working Time	Up to 4 hours
Application Method	Adhesive is rolled on using a 3/8-inch nap roller
RH Limit	99%
Use With	Armstrong Flooring Commercial & Residential Luxury Vinyl Tile & Commercial Vinyl Composition Tile
Warranty	Armstrong Flooring Commercial Resilient Warranty