


Product Information

- Product Lines - Coved Wall Base
- Construction - Thermoplastic Rubber
- Product Specifications - ASTM F1861, Type TP, Group 1, Style B
- Overall Thickness - 0.125 in. (3.18 mm)
- Installation - S-725 Wall Base Adhesive

Product Structures



Coved Wall Base

Packaging

Products	Height	Feet per Carton	Pieces per Carton
Coved - Sticks	4.0 in. (101.6 mm)	120 lin. ft. (36.57 m)	30
Coved - Rolls			1

Testing

Performance	Test Method	Requirement	Performance vs. Requirement
Composition of Materials	Certificate of Compliance	As specified	Meets
Wear Layer Thickness	ASTM F410	≥ 0.002 in.	Meets
Flexibility	ASTM F137	¼ inch mandrel no cracks or breaks in wear surface	Meets
Staining of adjacent surfaces induced by wall base	ASTM F1861 Section 12	No staining of adjacent surfaces	Meets
Resistance to Light	ASTM F 1515	Max. avg. ΔE ≤ 8	Meets
Resistance to Chemicals	ASTM F 925	No more than slight change in surface dulling, attack or staining	Meets
Dimensional Stability	ASTM F1861 Section 12	±0.25%	Meets
Height	ASTM F1861 Section 9	As specified, ±1% of nominal height	Meets
Thickness	ASTM F386	As specified, 0.080 in. +0.015/ -0.005 in. 0.25 in. + 0.015/ -0.015 in.	Meets
Length	ASTM F1861 Section 9	As specified, no less than nominal value	Meets
Additional Testing			
Fire Test Data – Flame Spread	ASTM E 648	0.45 W/cm² or more Class I	Meets
Fire Test Data – Smoke Evolution	ASTM E 662	450 or less	Meets

Sustainability

Certification Attribute	Standard	Feet per 3rd party Certification/Certifier
Low-Emitting Material	CDPH v1.2 (2017) a.k.a CHPS 01350	FloorScore®/SCS
Low-Emitting Adhesive (S-725)	CDPH v1.2 (2017) a.k.a CHPS 01350	FloorScore®/SCS

Sustainability Continued

Performance	Standard	Requirements	Performance vs. Requirements
TVOC Range	CDPH v1.2 (2017) a.k.a CHPS 01350	<0.5 mg/m³	Meets
Low Emitting Adhesives (S-725)	SCAQMD Rule #1168	Less than 50 g/L	S-725 Exceeds – 0 g/L
Fundamental Material Safety Toxic Material Reduction	WELL™ Feature 11 and 25	No asbestos, free of lead and phthalates (DEHP, DBP, BBP, DIDP, DNOP)	Meets

Limited Warranty

5-year Commercial Warranty when installed in strict accordance with the detailed instructions at [ArmstrongFlooring.com](https://www.armstrongflooring.com).

4 ft. Sticks - R41XX
Roll Cove - R48XX

R41SL R48SL Salt	R41PR R48PRI parchment	R41CI R48CI classic ivory	R41DS R48DS Desert	R41ES R48ES Essential Sand	R41CM R48CM Camel
R41CR R48CR Carbon Beige	R41PB R48PB Pebble	R41GR R48GR Greige	R41FX R48FX Flax	R41TR R48TR Turmeric	R41SD R48SD Saddle
R41BH R48BH Buffalo Hide	R41ML R48ML Molasses	R41WB R48WB Warm Black	R41FS R48FS Flagstone	R41EB R48EB Ebony	R41ND R48ND Indigo
R41GM R48GM Gray Mist	R41SW R48SW Stonewash	R41MG R48MG Metal Gray	R41SG R48SG Smokey Gray	R41CG R48CG Coastal Green	R41AN R48AN Almost Navy

Visit [ArmstrongFlooring.com](https://www.armstrongflooring.com)

for complete Product, Technical, Adhesives, Installation & Maintenance recommendations.