

S-385 Armstrong Satinkeeper Floor Polish, Lifeproof Floor Polish

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
Issue date: 6/6/2024 Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Substance
Substance name : S-385 Armstrong Satinkeeper Floor Polish, Lifeproof Floor Polish

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Cleaning/washing agents and additives
Restrictions on use : None known

1.3. Supplier

AHF Products
3840 Hempland Road
Mountville, PA, 17554
T (717) 251-1073

1.4. Emergency telephone number

Emergency number : CHEM-TEL 1-800-255-3924 OR 1-813-248-9585 (call collect)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Skin sensitization, Category 1 H317 May cause an allergic skin reaction
Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Warning
Hazard statements (GHS US) : H317 - May cause an allergic skin reaction
Precautionary statements (GHS US) : P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.
P272 - Contaminated work clothing must not be allowed out of the workplace.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352 - If on skin: Wash with plenty of water.
P321 - Specific treatment (see supplemental first aid instruction on this label).
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P363 - Wash contaminated clothing before reuse.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

S-385 Armstrong Satinkeeper Floor Polish, Lifeproof Floor Polish

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Name : S-385 Armstrong Satinkeeper Floor Polish, Lifeproof Floor Polish

Name	Product identifier	%	GHS US classification
Water	CAS-No.: 7732-18-5	50.99	Not classified.
Diethylene glycol monoethyl ether	CAS-No.: 111-90-0	2.95	Not classified.
Zinc(2+), tetraammine-, (T-4)-, carbonate (1:1)	CAS-No.: 38714-47-5	0.28 – 1.44	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Ethanol, 2-butoxy-, phosphate (3:1)	CAS-No.: 78-51-3	1.08	Not classified.

Full text of hazard classes and H-statements : see section 16

3.2. Mixtures

Not applicable

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs:
Get medical advice/attention.
First-aid measures after eye contact : Rinse eyes with water as a precaution.
First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact : May cause an allergic skin reaction.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media : Not determined.

5.2. Specific hazards arising from the chemical

Hazardous decomposition products in case of fire : Toxic fumes may be released.

S-385 Armstrong Satinkeeper Floor Polish, Lifeproof Floor Polish

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

5.3. Special protective equipment and precautions for fire-fighters

- | | |
|--------------------------------|--|
| Firefighting instructions | : Fight fire with normal precautions from a reasonable distance. |
| Protection during firefighting | : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. |

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- | | |
|------------------|---|
| General measures | : Do not handle until all safety precautions have been read and understood. |
|------------------|---|

6.1.1. For non-emergency personnel

- | | |
|----------------------|---|
| Emergency procedures | : Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray. |
|----------------------|---|

6.1.2. For emergency responders

- | | |
|----------------------|---|
| Protective equipment | : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection". |
|----------------------|---|

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- | | |
|-------------------------|---|
| Methods for cleaning up | : Take up liquid spill into absorbent material. |
| Other information | : Dispose of materials or solid residues at an authorized site. |

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- | | |
|-------------------------------|---|
| Precautions for safe handling | : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray. Wear personal protective equipment. |
| Hygiene measures | : Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. |

7.2. Conditions for safe storage, including any incompatibilities

- | | |
|--------------------|--|
| Storage conditions | : Store in a well-ventilated place. Keep cool. |
|--------------------|--|

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

S-385 Armstrong Satinkeeper Floor Polish, Lifeproof Floor Polish

No additional information available

Water (7732-18-5)

No additional information available

S-385 Armstrong Satinkeeper Floor Polish, Lifeproof Floor Polish

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Diethylene glycol monoethyl ether (111-90-0)

No additional information available

Ethanol, 2-butoxy-, phosphate (3:1) (78-51-3)

No additional information available

Zinc(2+), tetraammine-, (T-4)-, carbonate (1:1) (38714-47-5)

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: milky.
Color	: White
Odor	: Characteristic
Odor threshold	: No data available
pH	: 8.6
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: 100 °C
Flash point	: > 110 °C
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: 1.024
Solubility	: Dispersible.

S-385 Armstrong Satinkeeper Floor Polish, Lifeproof Floor Polish

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified.
Acute toxicity (dermal)	: Not classified.
Acute toxicity (inhalation)	: Not classified.

Water (7732-18-5)	
LD50 oral rat	> 90 ml/kg (Source: FOOD_JOURN)
Diethylene glycol monoethyl ether (111-90-0)	
LD50 oral rat	10502 mg/kg (Source: OECD_SIDS)
LD50 dermal rabbit	9143 mg/kg (Source: OECD_SIDS)
LC50 Inhalation - Rat	> 5240 mg/m ³ (Exposure time: 4 h Source: NLM_CIP)
ATE US (oral)	10502 mg/kg body weight
ATE US (dermal)	9143 mg/kg body weight

S-385 Armstrong Satinkeeper Floor Polish, Lifeproof Floor Polish

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Ethanol, 2-butoxy-, phosphate (3:1) (78-51-3)	
LD50 oral rat	3 g/kg (Source: NLM_CIP)
LD50 dermal rabbit	> 5000 mg/kg (Source: ECHA_API)
LC50 Inhalation - Rat	> 6.4 mg/l/4h
ATE US (oral)	3000 mg/kg body weight

Skin corrosion/irritation	: Not classified. pH: 8.6
Serious eye damage/irritation	: Not classified. pH: 8.6
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified.
Carcinogenicity	: Not classified.
Reproductive toxicity	: Not classified.
STOT-single exposure	: Not classified.
STOT-repeated exposure	: Not classified.
Aspiration hazard	: Not classified.
Viscosity, kinematic	: No data available
Symptoms/effects after skin contact	: May cause an allergic skin reaction.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.
-------------------	--

Diethylene glycol monoethyl ether (111-90-0)	
LC50 - Fish [1]	10000 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static] Source: EPA)
EC50 - Crustacea [1]	3940 – 4670 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 - Fish [2]	19100 – 23900 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [flow-through] Source: EPA)

Ethanol, 2-butoxy-, phosphate (3:1) (78-51-3)	
LC50 - Fish [1]	10.4 – 12 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

Diethylene glycol monoethyl ether (111-90-0)	
Partition coefficient n-octanol/water (Log Pow)	-0.8

Ethanol, 2-butoxy-, phosphate (3:1) (78-51-3)	
BCF - Fish [1]	(3.65 dimensionless)
Partition coefficient n-octanol/water (Log Pow)	3.75

12.4. Mobility in soil

No additional information available

S-385 Armstrong Satinkeeper Floor Polish, Lifeproof Floor Polish

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

In accordance with DOT / IMDG / IATA

14.1. UN number

Not regulated for transport

14.2. UN proper shipping name

Proper Shipping Name (DOT)	: Not applicable
Proper Shipping Name (TDG)	: Not applicable
Proper Shipping Name (IMDG)	: Not applicable
Proper Shipping Name (IATA)	: Not applicable

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : Not applicable

IMDG

Transport hazard class(es) (IMDG) : Not applicable

IATA

Transport hazard class(es) (IATA) : Not applicable

14.4. Packing group

Packing group (DOT)	: Not applicable
Packing group (IMDG)	: Not applicable
Packing group (IATA)	: Not applicable

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

DOT

No data available

IMDG

No data available

IATA

No data available

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

S-385 Armstrong Satinkeeper Floor Polish, Lifeproof Floor Polish

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 15: Regulatory information

15.1. US Federal regulations

S-385 Armstrong Satinkeeper Floor Polish, Lifeproof Floor Polish

SARA Section 311/312 Hazard Classes	Health hazard - Respiratory or skin sensitization
-------------------------------------	---

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

Water (7732-18-5)

Listed on Thailand Existing Chemicals Inventory (DIW)

Diethylene glycol monoethyl ether (111-90-0)

Listed on Thailand Existing Chemicals Inventory (DIW)

Ethanol, 2-butoxy-, phosphate (3:1) (78-51-3)

Listed on Thailand Existing Chemicals Inventory (DIW)

Zinc(2+), tetraammine-, (T-4)-, carbonate (1:1) (38714-47-5)

Listed on Thailand Existing Chemicals Inventory (DIW)

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases

H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects

Safety Data Sheet (SDS), USA - HSI

S-385 Armstrong Satinkeeper Floor Polish, Lifeproof Floor Polish

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable