

LUXURY FLOORING

Mixtera™ - Mirage, Mosaic, Prism, Tandem

Product Information

Construction - Solid Vinyl Tile (Luxury Vinyl Tile / LVT)

International Specifications - ASTM F 1700, Class III, Type B embossed surface


Overall Thickness - 0.100 in. (2.5 mm)

Wear Layer Thickness - 0.0020 in. (0.5 mm)

Factory Finish - Diamond 10® Technology

Installation - Adhesives: S-995, S-319 Roll Strong™, S-1000

Maintenance Options - No Polish - No Buff, Polish Optional



Packaging

Size	Pieces per Carton/Coverage	Shipping Weight per Carton
6 in. x 36 in. (152 mm x 914 mm)	24 / (36 sq. ft.) 5.02 m²	39 lbs. (17.73 kg)
18 in. x 36 in. (457 mm x 914 mm)	12 / (54 sq. ft.) 5.02 m²	55.80 lbs. (25.31 kg)

Testing

ASTM F1700			
Performance	Test Method	Requirement	Performance vs. Requirement
Thickness	ASTM F386	Nominal ±0.005 in.	Meets
Wear Layer Thickness	ASTM F410	0.020 in. (0.5 mm) minimum for Commercial Use	Meets
Size	ASTM F2421	± 0.016 in. per linear foot	Meets
Squareness	ASTM F2421	0.010 in. maximum	Meets
Residual Indentation	ASTM F1914	Average less than 8%	Meets
Chemical Resistance	ASTM F925	No more than slight change in surface dulling, attack or staining	Meets
Resistance to Heat	ASTM F1514	ΔE < 8 avg., max	Meets
Resistance to Light	ASTM F1515	ΔE < 8 avg., max	Meets
Additional Testing			
Static Load Resistance	ASTM F970*	≤ 0.005 in.	2000 psi
Dimensional Stability	Internal	≤ 0.018 in. per linear ft. MD ≤ 0.012 in. per lin. ft. AMD	Meets
Fire Test Data – Flame Spread	ASTM E648	0.45 W/cm² or more Class 1	Meets
Fire Test Data – Smoke Evolution	ASTM E662	450 or less	Meets
Fire Test Data – Canada	CAN/ULC S-102.2	Use dependent	Flame Spread - 5 Smoke Developed - 75
ADA Standards for Accessible Design	Chapter 3, Section 302.1	Floor surfaces shall be stable, firm and slip resistant	Meets
Static Coefficient of Friction**	ASTM D2047/UL 410	≥ 0.5	Meets
Acoustics	ASTM E492 ASTM E90 ASTM E2179	IIC ≥ 50 (International Building Code) STC ≥ 50 (International Building Code) Sound Transmission Reduction	Exceeds - IIC 53 Exceeds- STC 51 ΔIIC - 22 6 in. concrete, no ceiling with S-1840 Quiet Comfort Luxury Flooring Underlayment

LUXURY FLOORING

Mixtera™ - Mirage, Mosaic, Prism, Tandem

Sustainability

WELL v1 Feature

Air	Feature 04 - VOC Reduction	Mixtera	Contribution
	Feature 11 - Fundamental Material Safety	✓	Tested and third party certified by FloorScore® as complying with CDPH v1.2
	Feature 25 - Toxic Material Reduction	✓	Product is free of asbestos and added lead (Part 1)
		✓	Free of flame retardants (Part 2) and phthalates (Part 3)
Mind	Feature 97 - Material Transparency	✓	Readily available Health Product Declaration® (HPD) to 1000 ppm
	Feature 88 (Part 2) Biophilia I - Qualitative	✓	Products available that incorporate nature patterns
	Feature 99 - Beauty and Design II	✓	Patterns and colors to aid in wayfinding and spatial familiarity (Part 3)

WELL v2 Feature

Materials	Feature X01.1 Material Restrictions	Mixtera	Contribution
	Feature X05.1 Enhanced Material Restrictions	✓	Product is free of asbestos
	Feature X06.1 VOC Restrictions	✓	Free of flame retardants (Part 2) and phthalates (Part 3)
	Feature X06.2 VOC Restrictions	✓	Adhesives associated with product are tested and third party certified by FloorScore as complying with CDPH v1.2
	Feature X07.1 Material Transparency	✓	Flooring is tested and third party certified by FloorScore as complying with CDPH v1.2
Mind	Feature M02.1 Nature and Place	✓	Readily available Health Product Declaration (HPD) to 1000 ppm
Community	Feature C13 (Part 2) Accessibility and Universal Design	✓	Products available that incorporate nature patterns
			Provided patterns and colors to aid in wayfinding and spatial familiarity

LEED™ v4.1

	Mixtera
BPDO - EPD	Third party certified Product Specific
BPDO - Material Ingredient	HPD
BPDO - Sourcing	29% pre-consumer recycled content
Location of Manufacturer	USA
Low Emitting Flooring	Tested and third party certified by FloorScore as complying with CDPH v1.2
Low Emitting Adhesives	Tested and compliant to CDPH v1.2; Methylene Chloride and Perchloroethylene not intentionally added; FloorScore Certified
SCAQMD #1168 Compliant.	S-319 Roll Strong – 0 g/L
Adhesives meet <50 g/L requirement	S-995 - 0 g/L
	S-1000 – 0.1 g/L

Carbon Footprint

	Duo
Global Warming Potential, excluding Biogenic Carbon	0.64 Kg CO ₂ eq. / square foot
Raw Materials (A1) through Production (A3)	(6.88 Kg CO ₂ eq. / square meter)

Limited Warranty

20-year Commercial Warranty when installed in strict accordance with the detailed instructions.

Visit ArmstrongFlooring.com

for complete Product, Technical, Adhesives, Installation & Maintenance recommendations.

AF-1145-725

© 2025 AHF Products LLC.

FloorScore® is a registered trademark of the Resilient Floor Covering Institute. | LEED® is a registered trademark of the United States Green Building Council. The Health Product Declaration® logo is a registered trademark of HPD Collaborative. | All other trademarks are owned by AHF LLC.

*Testing at loads above 250 psi is outside the scope of the test method. Since testing is conducted on uninstalled flooring, results do not consider the performance of the adhesive, underlayment, or subfloor. These test results are not an indicator of the installed flooring system performance. **Using the James Machine as described in D2047 and as directed in UL 410 for floor covering materials (FCM) using a leather foot under dry conditions. The application of site-applied floor sealers, polishes and other types of finishes routinely used to maintain resilient flooring materials will change the walking surface and consequently the SCOF value.



MADE IN THE USA
with global and
domestic components