

Light Reflectivity

Luxury Vinyl Tile

Conjunction™ 4.5 mm

All light reflectivity values listed are based on a percentage system, the higher the percentage (e.g., 20-24, 35-39), the higher the light reflectance of the floor. It is measured per ASTM E1349, *Standard Test Method for Reflectance Factor and Color by Spectrophotometry Using Bidirectional (45°: 0° or 0°: 45°) Geometry*. Research indicates reflectance can help drive daylight further into space and reduce reliance on artificial lighting, resulting in reduced electricity usage and costs. Glare from flooring is a characteristic of glossy finishes, not reflectance. Flooring in lighter colors with a matte finish have high reflectance values, but do not add to glare. Flooring with light reflectivity values greater than 25% can contribute to LEED® Interior Lighting Credit.

Value	SKUs
0-9	L7125, L7133
10-14	L7132, L7521
15-19	L7514, L7273, L7253
20-24	L7154, L7520
25-29	L7539, L7251, L7519, L7331
30-34	L7252, L7511
35-39	L7510, L7518, L7140
40-44	-
45-49	L7522
50-54	L7528
55-59	-
60-64	-
65-69	-
70-74	-

ArmstrongFlooring.com

for complete Product, Technical, Adhesives, Installation, and Maintenance recommendations.

LEED® is a registered trademark of the United States Green Building Council.

©2026 All trademarks are owned by AHF, LLC, or its subsidiaries or affiliates.