

## Light Reflectivity – TimberTones®

All light reflectivity values listed are based on a percentage system, the higher the percentage (e.g. 20-24, 35-39), the higher the light reflectance of the floor. It is measured by ASTM E1349, Standard Test Method for Reflectance Factor and Color by Spectrophotometry Using Bidirectional (45°:0° or 0°:45°) Geometry.

Research indicates reflectance can help drive daylight further into space and reduce reliance on artificial lighting, resulting in reduced electricity usage and costs. Glare from flooring is a characteristic of glossy finishes, not reflectance. Flooring in lighter colors with a matte finish have high reflectance values, but do not add to glare. Flooring with light reflectivity values greater than 25% can contribute to the LEED® Interior Lighting Credit.

Value	TimberTones® Skus
0-9	EK7CP488W
10-14	LM19W-806W, EK7CP423W, EK7CP443W, EK7LD687W
15-19	LM19P-546W, LM22K-213S, EK7CP483W
20-24	LM19C-466W, LM19P-536W, LM19P-556W, EK6LD607W
25-29	LM19P-526W, LM22A-223W, LM22H-253S, LM22M-233W
30-34	LM19M-416W, EK7CP473W
35-39	LM22B-283W, EK7CP453W
40-44	--
45-49	--
50-54	--
55-59	--
60-64	--
65-69	--
70-74	--