

Light Reflectivity

3.2 mm LVT with Diamond 10® Technology

Natural Creations®

All light reflectivity values listed are based on a percentage system, the higher the percentage (e.g. 20-24, 35-39), the higher the light reflectance of the floor. It is measured per ASTM E1349, Standard Test Method for Reflectance Factor and Color by Spectrophotometry Using Bidirectional (45°:0° or 0°:45°) Geometry.

Research indicates reflectance can help drive daylight further into space and reduce reliance on artificial lighting, resulting in reduced electricity usage and costs. Glare from flooring is a characteristic of glossy finishes, not reflectance. Flooring in lighter colors with a matte finish have high reflectance values, but do not add to glare. Flooring with light reflectivity values greater than 25% can contribute to the LEED® Interior Lighting Credit.

VALUE	SKUS
0-9	NA225, NA542, NA553
10-14	NA121, NA194, NA521, NA532, NA537, NA538, NA540
15-19	NA120, NA181, NA191, NA514, NA536
20-24	NA171, NA180, NA193, NA331, NA516, NA517, NA520, NA534, NA541, NA543
25-29	NA190, NA511, NA513, NA515, NA533, NA535, NA539
30-34	NA512, NA519
35-39	NA526, NA550
40-44	NA170, NA310, NA518, NA523, NA524
45-49	NA330, NA522, NA525, NA527, NA544, NA549
50-54	NA528, NA529, NA547, NA548
55-59	--
60-64	--
65-69	--
70-74	--