

Light Reflectivity

Slip-Retardant Tile

Safety Zone™

All light reflectivity values listed are based on a percentage system, the higher the percentage (e.g., 20-24, 35-39), the higher the light reflectance of the floor. It is measured per ASTM E1349, *Standard Test Method for Reflectance Factor and Color by Spectrophotometry Using Bidirectional (45°: 0° or 0°: 45°) Geometry*. Research indicates reflectance can help drive daylight further into space and reduce reliance on artificial lighting, resulting in reduced electricity usage and costs. Glare from flooring is a characteristic of glossy finishes, not reflectance. Flooring in lighter colors with a matte finish have high reflectance values, but do not add to glare. Flooring with light reflectivity values greater than 25% can contribute to LEED® Interior Lighting Credit.

Value	SKUs
0-9	51910SZ, 57004
10-14	51915SZ
15-19	-
20-24	-
25-29	51804SZ, 51927SZ, 57008
30-34	51903SZ
35-39	51904SZ
40-44	51830SZ, 57001
45-49	51908SZ
50-54	51810SZ, 51836SZ, 51858SZ, 51860SZ, 51861SZ
55-59	51911SZ
60-64	51839SZ, 51941SZ, 59234SZ
65-69	51899SZ, 52513SZ
70-74	51933SZ

ArmstrongFlooring.com

for complete Product, Technical, Adhesives, Installation, and Maintenance recommendations.

LEED® is a registered trademark of the United States Green Building Council.

©2025 All trademarks are owned by AHF, LLC, or its subsidiaries or affiliates.