

Light Reflectivity

Vinyl Composition Tile

Premium Excelon® Stonetex™

All light reflectivity values listed are based on a percentage system, the higher the percentage (e.g., 20-24, 35-39), the higher the light reflectance of the floor. It is measured per ASTM E1349, *Standard Test Method for Reflectance Factor and Color by Spectrophotometry Using Bidirectional (45°: 0° or 0°: 45°) Geometry*. Research indicates reflectance can help drive daylight further into space and reduce reliance on artificial lighting, resulting in reduced electricity usage and costs. Glare from flooring is a characteristic of glossy finishes, not reflectance. Flooring in lighter colors with a matte finish have high reflectance values, but do not add to glare. Flooring with light reflectivity values greater than 25% can contribute to LEED® Interior Lighting Credit.

Value	SKUs
0-9	52144
10-14	52161
15-19	52147, 52149
20-24	52160
25-29	52125, 52166
30-34	52155
35-39	52126
40-44	52122, 52143
45-49	-
50-54	52128
55-59	-
60-64	52127, 52139
65-69	52140
70-74	-

ArmstrongFlooring.com

for complete Product, Technical, Adhesives, Installation, and Maintenance recommendations.

LEED® is a registered trademark of the United States Green Building Council.

©2026 All trademarks are owned by AHF, LLC, or its subsidiaries or affiliates.