



## PRODUCT INFORMATION

### SHINEKEEPER LONG LASTING FLOOR POLISH

#### Description

SHINEKEEPER LONG LASTING FLOOR POLISH is a metal cross-linked acrylic floor finish which has been formulated to give a fast film build on Armstrong vinyl sheet and tiles. SHINEKEEPER provides the ideal surface for Armstrong vinyl sheet and tiles in most situations giving the best balance between “easy to scratch – easy to repair”, and “hard to scratch – hard to repair”.

SHINEKEEPER responds well to spray buffing and with all speeds of buffing equipment from 350 – 2000 rpm for use in commercial, industrial and institutional applications.

SHINEKEEPER has been formulated in a way that it will stand up to traffic with minimum maintenance, ie: where machine buffing is seldom or rarely performed eg: domestic homes.

SHINEKEEPER exhibits exceptional wear properties due to the tough flexible film that shows good resistance to black heel marking, scuffs and powdering.

#### Physical Properties

Non-Volatile Matter	20%
pH	9.0 ± 0.5
Specific Gravity	1.030
Drying Time	30 minutes – dependant upon conditions
Coverage	50 – 80m <sup>2</sup> /litre

#### Available Container Sizes

1 litre, 4 litres, 25 litres

#### Directions for Use

After initial preparation using NEW BEGINNING EXTRA STRENGTH CLEANER AND STRIPPER (not necessary for products factory coated with Armstrong Fast Start, consult label or Technical Data for procedures), apply three coats of SHINEKEEPER using a lambs-wool applicator or clean cotton mop, allowing one hour between coats.

**Note:** If floor is treated with 2001 PREMIUM SEALER prior to SHINEKEEPER, then only two coats of SHINEKEEPER are required.

For commercial applications a total to five (5) coats of SHINEKEEPER are recommended for optimum performance.

Daily or periodic maintenance should be effected using Armstrong ONCE N' DONE NO RINSE FLOOR CLEANER in accordance with directions.