



LUXURY VINYL TILE & PLANK

MAINTENANCE RECOMMENDATIONS

MAINTENANCE RECOMMENDATIONS

Maintenance

Your Armstrong floor has an impervious PVC wear layer which makes the floor tough and easier to clean. Effective maintenance of your flooring is common sense, all good maintenance procedures consist of thorough dirt and grit control, removal of spills and the protection of the floor surface. Walk off mats can help considerably reduce the amount of grit brought in by foot traffic, sweeping, mopping and vacuuming all help to control grit. Damp mopping, spot cleaning and washing will remove most spills and stains.

Initial cleaning after installation

- > Remove all loose dirt by sweeping or vacuuming with suitable domestic vacuum cleaner (ensure the 'smooth flooring setting' is selected).
- > Remove any residual adhesive from the surface following the adhesive manufacturers instructions.

Preparation for use

- > Initial treatment with suitable emulsion polish will help protect the floor from marks and scratches, enhance the surface finish and make routine maintenance easier. Apply two coats according to the manufacturers instructions. Only apply the second coat cross-directionally when the first has dried thoroughly.
- > Damp mop the floor with a dilute neutral (pH 6-8) detergent solution, carefully removing black marks and excessive soil by gentle scrubbing with a non abrasive material.
- > Rinse the floor and allow to dry.

Subsequent maintenance depends on the amount and type of traffic, the provision of adequate grit control and the maintenance equipment available.

Regular Maintenance

- > Sweep or vacuum the floor to remove all loose dirt and grit.
- > Damp mop the floor with a solution of detergent recommended for vinyl flooring – always read the label to ascertain suitability and follow the manufacturers instructions for application.
- > Rinse and allow to dry.
- > Buff the floor with a dry soft mop or cloth.
- > In high traffic areas it may be advisable to utilise a good quality floor polish — again, always read the label to ascertain suitability and follow the manufacturers instructions for application.

Caution

- > Cigarettes and other hot objects of high temperature (>500°C) can scar the surface of the floor.
- > Certain types of rubber should be avoided unless it is known they are non-staining. (e.g. rubber backed mats)
- > Asphalt and bitumen type products are known to cause PVC to yellow. Care must be taken to avoid stains from these types of products, e.g. residue trodden in from newly laid drives, roads etc.

Important

Please note that all smooth flooring can be slippery when wet. All necessary precautions should be taken when maintaining flooring of this type. All spillages should be removed as soon as possible.

Armstrong World Industries (India) Pvt. Ltd.

Boomerang, A-304, Chandivali Farm Road (near Chandivali Studio) Andheri (E), Mumbai - 400 072
Tel: 022-3048 0800, Fax: 022-3046 0439 / 2491 3604 | e-mail : helpdeskindia@armstrong.com

Branches:

Ahmedabad : +91-85111 46309	Bengaluru : +91-80-2657 6367	Chandigarh : +91-172-2633 680
Chennai : +91-44-4217 5303	Gurgaon : +91-93126 73142	Hyderabad : +91-40-3200 9868
Pune : +91-20-3250 2404	Kolkata : +91-33-2401 4755	Lucknow : +91-522-220 1143

Representatives:

Bhopal : +91-93237 99834	Bhubaneswar : +91-99039 20499	Cochin : +91-99477 87111
Coimbatore : +91-93677 81490	Dehradun : +91-93169 19120	Goa : +91-93255 02140
Guwahati : +91-99030 81018	Indore : +91-93237 99834	Jaipur : +91-93525 69512
Jammu : +91-93169 19120	Ludhiana : +91-93169 19120	Nagpur : +91-93237 99834
Nashik : +91-93255 02140	Patna : +91-93126 73148	Raipur : +91-93255 02140
Ranchi : +91-99039 20499	Surat : +91-85111 46309	Trivandrum : +91-99477 87111
Vizag : +91-93938 96055		