

Installation, Maintenance & Warranty

Vinyl Sheet

INSTALLATION

- **Job Condition**

Subfloor / underlayment shall be hard, levelled, dry, clean and smooth. They shall be free from paint, varnish, solvents, wax, oil, existing adhesive residue or any other foreign matter. Acclimatize all flooring materials and adhesives to room temperature at least for 72 hours prior to installation.

Note : Cementitious self levelling compound should be used to achieve zero level sub-floor.

- **Procedure**

Installation shall be carried out according to Armstrong's recommendations (www.armstrong.co.in). The recommended adhesive should be used to ensure satisfactory installation.

- **Adhesive**

Armstrong recommends VOC free water based adhesive like Arobond 44 or Arofine Polymer or equivalent. Rubber based adhesives or any other solvent based adhesives should not be used with Vinyl Sheet installation. Rubber based adhesives should be limited for accessories installation only.

MAINTENANCE

- Dry mop with microfiber cloth thoroughly
- Damp mop with a dilute neutral detergent solution
- Black marks and dirty spots can be treated by spot scrubbing
- Use Armstrong "Cleaner", "Protect", "Shinekeeper" and "Stripper" for maintenance.

WARRANTY

Armstrong warrants its product to be free from manufacturing defects for five (5) years from the date of purchase. For detail warranty please contact Armstrong sales representative.