




Specification according to EN 649

Characteristics	Standard	Unit	Result
Type of floor covering	ISO 10581-EN 649		Homogeneous vinyl sheet
Material			Polyvinyl chloride
Polyurethane coating			TrueShield
<b>Safety Criteria</b>			
Flammability	GB 8624-2012	class	B1
	EN 13501-1	class	Bfl-S1
Dynamic coefficient of friction	EN 13893	class	DS
<b>General Properties</b>			
Roll width	ISO 24341-EN 426	m	2
Roll length	ISO 24341-EN 426	m	13 - 20
Overall thickness	ISO 24346-EN 428	mm	2.0
Total weight	ISO 23997-EN 430	kg/m <sup>2</sup>	2.75
Wear resistance	EN 660-2	group	T
Dimensional stability	ISO 23999-EN 434	-	X: < 0.4%; Y: < 0.4%
Binder content	EN ISO 10581	Type	Type1 >55%
Color fastness	ISO 105-B02	rating	>6
Impact sound reduction	ISO 10140 ISO 717-2	dB	3
Resistance to staining	EN 423		No stain
Classification	ISO 10874-EN 685	class	Domestic: 23 heavy Commercial: 34 very heavy Industrial: 43 heavy
<b>Additional property</b>			
Underfloor heating		Castor Chair	
Chemical resistance		Antistatic	