

# MAINTENANCE RECOMMENDATIONS FOR HETEROGENEOUS SHEET

**Timberline<sup>®</sup> Plus, Translations<sup>®</sup> Plus, Timberline<sup>®</sup>, Translations<sup>®</sup>**


## Initial Care:

After installation is completed:

1. Remove all debris (sweep or vacuum).
  2. Damp mop using Armstrong Flooring **Once 'n' Done Floor Cleaner** (\*or a pH 7.0-8.5 neutral cleaner).
- Allow 48 hours before carrying out the following:
1. Sweep or vacuum
  2. Damp mop or light scrub if necessary. Wet scrub using automatic scrubbing machine or single disc polisher ≤600RPM and Armstrong Flooring **Once 'n' Done Floor Cleaner\***.


## Routine care:

**Daily:** Sweep, vacuum, static mop. Regularly damp mop, wet scrub and burnish; use **Once 'n' Done Floor Cleaner** (or a pH 7.0-8.5 neutral cleaner). Frequency and type of maintenance required depends on traffic flow, application, environmental conditions and customer requirements. **Light and accent colours** can require more maintenance, where practical choose darker, more camouflaging colours.



### Daily:

- Sweep, mop, vacuum thoroughly to remove all dirt and dust.




### Daily / Regular:

- Damp Mop (Nylon/Rayon/Microfibre) and **Once 'n' Done Floor Cleaner\*** (\*or a pH 7.0-8.5 neutral cleaner).

### Regular:

- Spot scrub edges & fixtures using soft bristled broom and **Once 'n' Done Cleaner\*** (\*or a pH 7.0-8.5 neutral cleaner).



### Regular: Large & unobstructed areas.

- Wet Scrub using automatic scrubbing machine or single disc polisher ≤600RPM (use medium nylon brush) and **Once 'n' Done Floor Cleaner \*** (\*or a pH 7.0-8.5 neutral cleaner).

**For further Armstrong Flooring information:**

Free call 1800 632 624

[www.armstrongflooring.com.au](http://www.armstrongflooring.com.au)

# MAINTENANCE RECOMMENDATIONS FOR ARMSTRONG FLOORING PRODUCTS

## PROTECTING YOUR INVESTMENT

### Protection:

All vinyl flooring should be protected during the construction period.

Armstrong Flooring **DOES NOT** recommend the use of plastic materials for the protection of vinyl floor or wall products during construction (e.g. builder's plastic, corflute<sup>®</sup>, sticky back carpet or vinyl protector or films), these materials can damage the floor/wall.

Armstrong Flooring recommends the use of the lining felt from inside the roll as surface protection.

Alternatively the use of cardboard or paper products would be acceptable.

Where additional or solid protection is required first install lining felt, cardboard or paper and then rigid material over this (plywood, hardboard, corflute<sup>®</sup> etc).

**ENSURE** surface protection is applied over clean floors only.

**DO NOT** tape/stick protection directly to the floor

**DO NOT** allow water to sit on or under the protection materials (this could damage the floor and/or cloud the protective polyurethane).

**DO** use walk-off mats that are as wide as the doorway entrances and long enough (min. 3 average paces) to trap dirt before reaching the resilient floor. Ensure that walk-off mats are cleaned frequently.

Sand and grit are abrasive and can damage floors; stopping dirt at the entrance means less dirt trafficked through the building, protecting your investment and helping keep maintenance costs down.

Ensure all furniture legs have well maintained non-abrasive feet. Exposed metal legs can damage flooring.

**DO NOT** leave rubber products such as chair feet, tyres & mats in contact with the vinyl floor, these can cause staining.

### Stain Removal:

Treatment should be carried out when stains are fresh, immediately remove contaminant. Spot clean with a neutral floor cleaner using soft nylon brush. After stains have been removed, rinse floor with clean water and allow to dry.

### Warnings & General Hints:

1. **DO NOT USE:** Highly acidic, alkali, caustic or solvent agents such as hydrochloric/sulfamic acid, toilet bowl cleaner, paint stripper, benzene, toluol, acetone or strong scouring powders, as these will damage the floor.
2. Adhesive residue may be removed using a clean white cloth dampened with small amounts of mineral turps, carefully following warnings on container, immediately rinse with clean water (test in inconspicuous area first)
3. Auto scrubbing in unobstructed areas takes approximately 20% of the time of damp mopping. For maximum efficiency use damp mopping in obstructed areas only.
4. Spot mopping / spot scrubbing should be used when necessary. **Spillages** – post wet floor signs and wipe up immediately. Allow to dry and remove signs.

**For further Armstrong Flooring information:**  
Free call 1800 632 624  
[www.armstrongflooring.com.au](http://www.armstrongflooring.com.au)