



ARMSTRONG FLOORING – LUXURY VINYL PLANK

NATURAL CREATIONS® 2.5mm

NATURAL CREATIONS® XL 5.0mm

Maintenance Instructions

MAINTENANCE INSTRUCTIONS

Armstrong Flooring – Luxury Vinyl Plank/Tile

MAINTENANCE

NATURAL CREATIONS 2.5mm LUXURY VINYL PLANK/TILE AND NATURAL CREATIONS XL 5.0mm PLANK/TILE

Initial Care

After installation is completed, the following must be performed:

1. Remove all debris with an electrostatic mop or vacuum
2. Use a damp mop to mop with Armstrong Flooring Once n' Done (or similar pH 7.0-8.5 neutral cleaner).

Regular Maintenance

- Sweep or vacuum your new floor regularly to remove loose dirt which can scratch your floor.
 - The use of steam mops or similar is not recommended.
- Wipe up spills as soon as possible.
- Never use highly abrasive scrubbing tools on any resilient floor.
- Damp mop your floor regularly with a neutral detergent such as Armstrong Flooring Once 'n' Done floor cleaner (or similar pH 7.0-8.5 neutral cleaner).

- Do NOT use detergents, abrasive cleaners, or “mop and shine” products. These products may leave a dull film on your floor.
- Do NOT use paste wax or solvent based polishes.
- Do not use highly alkaline ‘floor strippers’ to clean the floor covering. Highly alkaline solutions have the potential to damage the adhesive bonds between the planks.

Proactive protection of your floor

- Use floor protectors under furniture to reduce indentation. As a general rule of thumb, the heavier the item, the wider the floor protector needed.
- Place a walk-off mat at outside entrances to reduce the amount of dirt brought into your home. Armstrong Flooring strongly recommends the use of mats without a latex or rubber (particularly black) backing since these can cause permanent discoloration.
- All Armstrong Flooring floor care products have been specifically developed to care for Armstrong Flooring products.

ARMSTRONG FLOORING PTY LTD

FLOORCOVERINGS, ADHESIVES & ACCESSORIES MANUFACTURED IN AUSTRALIA AFTER 1st JANUARY, 1984 DO NOT CONTAIN ASBESTOS



WARNING

Vinyl flooring and adhesives manufactured in Australia prior to 1st January, 1984 may contain asbestos.

Do not sand, dry sweep, dry scrape, drill, saw, beadblast, or mechanically chip or pulverise existing resilient flooring, backing, lining felt or asphaltic ‘cut-back’ adhesives.

These products may contain either **asbestos fibres** or **crystalline silica**.

Avoid creating dust. Inhalation of such dust is a cancer and respiratory tract hazard.

Unless positively certain that the product to be removed is a non-asbestos containing material, you must presume it contains asbestos. Regulations may require that the material be tested to determine asbestos content.

Where do I go to find out more about asbestos?

Asbestos Awareness www.asbestosawareness.com.au – provides information

on a state by state basis about the dangers of asbestos, asbestos removal, who to contact and other important information.

NOTE: Vinyl flooring manufactured in Australia after January 1, 1984, **DOES NOT** contain asbestos. However, regulations, codes and directives as to the best method of handling asbestos do exist and it is the obligation of the installer to ensure that practices used are safe, without risk to health, and meet all legal requirements.

Disclaimer—Asbestos issues

The warnings and guidance contained in these instructions in relation to the potential for asbestos in floorcovering materials are given in good faith. However, regulations, codes and directives as to the best method of handling asbestos are under continual revision. It is the obligation of the installer to ensure that practices used are safe, without risk to health, and meet all legal requirements.

Armstrong Flooring Pty Ltd accepts no liability for any loss, costs, expense or injury, however incurred, arising from the presence of any asbestos in any floorcovering materials or asphaltic ‘cut-back’ adhesives and/or any reliance placed upon the procedures and recommended practices contained in these instructions.

Armstrong Flooring Pty Ltd

29 – 39 Mills Road, Braeside, 3195 Victoria Australia

For further information and samples:

Australia Freecall 1800 632 624

Email customer_services@armstrongflooring.com or contact us on the web

www.armstrongflooring.com.au