

### Product Information

**Construction** - Vinyl Composition Tile

**Product Line** - Safety Zone™ Tile

**International Specifications** - ASTM F1066 - Class 2 Through Pattern

**Overall/Wear Layer Thickness** - 1/8" (3.2 mm)


**Factory Finish** - Fast Start®

**Installation** - Full Spread Adhesives S-515, S-525, S-700, S-750 & S-240, Flip® Spray Adhesive

**Maintenance Options** - Polish

Exclusive Textured,  
Particle-Enhanced Surface

Through-Pattern Wear Layer



### Packaging

Size	Pieces per Carton/Coverage	Shipping Weight per Carton
12" x 12" (305 mm x 305 mm)	12" x 12" - 12 (45 sq. ft.) 4.18 m <sup>2</sup>	61 lbs. (27.7 kg)

### Testing

Performance	Test Method	Requirement	Performance vs. Requirement
Thickness	ASTM F386	Nominal ± 0.005 in.	Meets
Size	ASTM F2055	± 0.016" per linear foot	Meets
Squareness	ASTM F2055	0.010" maximum	Meets
Dimensional Stability	ASTM F2199	≤ 0.024" per linear foot max.	Meets
Chemical Resistance	ASTM F925	No more than slight change in surface dulling, attack or staining	Meets
Resistance to Heat	ASTM F1514	ΔE ≤ 8	Meets
Static Load Resistance @ 125	ASTM F970	≤ 0.005"	Meets
Additional Testing			
Static Load Resistance	ASTM F970*	≤ 0.005"	800 psi
Fire Test Data - Flame Spread	ASTM E648	0.45 W/cm <sup>2</sup> or more Class 1	Meets
Fire Test Data - Smoke Evolution	ASTM E662	450 or less	Meets
Fire Test Data - Canada	CAN/ULC S-102.2	Use dependent	Flame Spread - 0   Smoke Developed - 30
Static Coefficient of Friction**	ASTM D2047/UL 410	≥ 0.5	Meets
ADA Standards for Accessible	Design Chapter 3 Section 302.1	Floor surfaces shall be stable, firm and slip-resistant	Meets

### Maritime Usage

Marine Equipment Directive (MED) 96/98/EC	Certificate No. 164.117/1121/WCL MED015QA
IMO Resolution A653 (16)	
Surface Flammability Test - IMO Resolution MSC 61(67) Annex 1 Part 5 and Annex 2	Passes
Smoke and Toxicity Test - IMO Resolution MSC 61(67) Annex 1 Part 2 and Annex 2	Passes
Safety Of Life at Sea (SOLAS) 1974 Regulation	
II-2/3.40.5.3.2.4	
II-2/5.3.2.4	Compliant
II-2/6.2	
United States Coast Guard	Approval No. 164.117/1121/WCL MED015TE

### Sustainability

#### WELL v1 Feature

<b>Air</b>	Feature 04 - VOC Reduction
	Feature 11 - Fundamental Material Safety
	Feature 25 - Toxic Material Reduction
<b>Mind</b>	Feature 97 - Material Transparency
	Feature 88 (Part 2) Biophilia I - Qualitative
	Feature 99 - Beauty and Design II

#### Safety Zone Tile

✓
✓
✓
✓
✓
✓

#### Contribution

Tested and third party certified by FloorScore as complying with CDPH v1.2
Product is free of asbestos and added lead (Part 1)
Free of flame retardants (Part 2)
Readily available Health Product Declaration (HPD) to 1000 ppm
Products available that incorporate nature patterns
Provided patterns and colors to aid in wayfinding and spatial familiarity (Part 3)

#### WELL v2 Feature

<b>Air</b>	Feature X12 - Short Term Emission Control
	Feature X11 Long-Term Emission Control
	Feature X01 Fundamental Material Precautions
	Feature X10 Volatile Organic Compound
<b>Materials</b>	Feature X14 Material Transparency
	Feature M02 Access to Nature
<b>Mind</b>	Feature C13 (Part 2) Accessibility and Universal Design

#### Safety Zone Tile

✓
✓
✓
✓
✓
✓
✓

#### Contribution

Adhesives associated with product are tested and third party certified by FloorScore as complying with CDPH v1.2
Flooring is tested and third party certified by FloorScore as complying with CDPH v1.3
Product is free of asbestos
Free of flame retardants (Part 2)
Readily available Health Product Declaration (HPD) to 1000 ppm
Products available that incorporate nature patterns
Provided patterns and colors to aid in wayfinding and spatial familiarity

#### LEED™ v4.1

BPDO - EPD
BPDO - Material Ingredient
BPDO - Sourcing
Location of Manufacturer
Low Emitting Flooring
Low Emitting Adhesives
SCAQMD #1168 Compliant.
Adhesives meet >50 g/L requirement.

#### Safety Zone Tile

Product Specific certified by ASTM International
HPD
Recycled Content – 40% Pre-Consumer
Extended Producer Responsibility – On&On™ Recycling Program
USA
Tested and third party certified by FloorScore as complying with CDPH v1.2
Tested and compliant to CDPH v1.2; Methylene Chloride and Perchloroethylene not intentionally added; FloorScore Certified
S-515 Exceeds - 0 g/L
S-525 Exceeds - 16 g/L
S-700 Exceeds - 0 g/L
S-750 Exceeds - 5 g/L
S-240 Exceeds - 10 g/L
Flip® Exceeds - 0 g/L

### Limited Warranty

5-year Commercial Warranty when installed in strict accordance with the detailed instructions.

### Visit ArmstrongFlooring.com

for complete Product, Technical, Adhesives, Installation & Maintenance recommendations.

F-9418-321

Printed in USA. | Armstrong and the Armstrong logo are under license from AWI Licensing LLC. | All other trademarks are owned by AFI Licensing LLC. | © 2021 AFI Licensing LLC. FloorScore® is a registered trademark of the Resilient Floor Covering Institute. | LEED® is a registered trademark of the United States Green Building Council.

\*Testing at loads above 250 psi is outside the scope of the test method. Since testing is conducted on uninstalled flooring, results do not consider the performance of the adhesive, underlayment, or subfloor. These test results are not an indicator of the installed flooring system performance. \*\*Using the James Machine as described in D2047 and as directed in UL 410 for floor covering materials (FCM) using a leather foot under dry conditions. The application of site-applied floor sealers, polishes and other types of finishes routinely used to maintain resilient flooring materials will change the walking surface and consequently the SCOF value.

