

Light Reflectivity

Rejuvenations™ with Diamond 10® Technology

All light reflectivity values listed are based on a percentage system, the higher the percentage (e.g. 20-24, 35-39), the higher the light reflectance of the floor. It is measured per ASTM E1349, *Standard Test Method for Reflectance Factor and Color by Spectrophotometry Using Bidirectional (45°:0° or 0°:45°) Geometry*. Research indicates reflectance can help drive daylight further into space and reduce reliance on artificial lighting, resulting in reduced electricity usage and costs. Glare from flooring is a characteristic of glossy finishes, not reflectance. Flooring in lighter colors with a matte finish have high reflectance values, but do not add to glare. Flooring with light reflectivity values great than 25% can contribute to the LEED® Interior Lighting Credit.

Value	Sku Numbers
0-9	37504, 37506, 37509, 37510, 37520, 38524, 38530
10-14	37505, 37508, 37517, 37519, 37527, 37528, 37529, 37530, 37534, 37535 37536, 34506, 34512, 38510, 38519
15-19	37516, 37518, 37533, 37537, 38513, 38520, 38523, 38526, 38529
20-24	37503, 37507, 34505, 38509, 38511, 38515, 38518, 38521, 38525, 38527 38531
25-29	37501, 37526, 37532, 38504, 38505, 38514, 38516, 38522, 38528, 38535
30-34	37502, 34501, 34504, 34511, 38506, 38512, 38517, 38534
35-39	37524, 38503, 38532, 38533
40-44	37523, 37525, 38501, 38502, 38508
45-49	
50-54	34503, 34510
55-59	34507, 34509
60-64	
65-69	
70-74	
75-79	