

S-599 ChoiceStrong™



CAUTION

S-599 **EYE AND SKIN IRRITANT**

STIR WELL BEFORE USING.

For use with the following Installation Systems:

- Commercial Vinyl-Backed
- Commercial Heterogeneous and Inlaid
- Residential LVT

DESCRIPTION:

Type:	Water-based resin
Color:	Creamy beige
Taggants:	Yes — blue glitter
Trowel:	S-891 Notched Steel Trowel or S-892 Replaceable Blade Trowel; fine notch (1/32" deep, 1/16" wide, 5/64" apart), U-notch
Coverage:	250–300 sq. ft./gallon (23–28 sq. m)
Units:	1 gallon (3.78 L) and 4 gallons (15.14 L)
Open Time:	Porous substrates — Set-in-wet: Minimum 10–20 minutes Nonporous substrates — Dry-to-touch: 30 minutes or more
Working Time:	Up to 1 hour (May vary based on job conditions, temperature, humidity, air circulation, etc.)
Shelf Life:	2 years, unopened
Freeze/Thaw Stable:	Yes, to 10° F (-12° C)
VOC Content:	< 14 g/L; calculated and reported, SCAQMD 1168
Clean Up:	Wet — clean, white cloth with neutral detergent and water Dry — clean, white cloth and mineral spirits
Subfloors:	All grade levels of concrete, existing resilient floors, ceramic, terrazzo, marble, steel, stainless steel, aluminum, polymeric poured floors and suspended wood Radiant Heated subfloors where the surface temperature does not exceed 85° F (29° C)
Advantages:	For Full Spread and Perimeter Plus systems Moisture and alkali resistant Strong, early grab AGIS Guarantee Nonflammable, ammonia-free, and low odor Contains low or no organic solvents