

Flip® Spray Adhesive



CAUTION

FLIP EYE AND SKIN IRRITANT

For use with the following Installation Systems:

- Residential Luxury Vinyl Tile
- Commercial Vinyl-Backed
- Commercial Heterogeneous and Inlaid
- Commercial Vinyl Composition Tile

DESCRIPTION:

Type:	Spray Adhesive
Color:	White
Taggants:	None
Trowel:	N/A
Coverage:	140–150 sq. ft./can (13–16 sq. m) Luxury Vinyl Tile and Commercial Vinyl Sheet 160–185 sq. ft./can(16–19 sq. m) Vinyl Composition Tile
Units:	22 oz. can
Open Time:	Until dry-to-touch: approximately 30 minutes or more
Working Time:	Up to 4 hours (May vary based on job conditions, substrates, temperature and humidity)
Shelf Life:	1 year, unopened
Freeze/Thaw Stable:	No, keep from freezing Store inside at a temperature of 60–100° F.
VOC Content:	Zero g/L; calculated and reported, SCAQMD 1168
Clean Up:	Wet — clean, white cloth with neutral detergent and water Dry — clean, white cloth and mineral spirits
Subfloors:	All grade levels of concrete, existing resilient floors, ceramic, terrazzo, marble, polymeric poured floors and suspended wood
Advantages:	Moisture and alkali resistant Strong, early grab AGIS Guarantee Nonflammable, ammonia-free and low odor Contains low or no organic solvents Suitable for heavy rolling loads Allows immediate traffic Vinyl sheet can be heat welded immediately

DO NOT USE OVER: Concrete with excessive moisture and/or alkali; existing cushion-backed resilient flooring; substrates treated with fire-retardant chemicals, fungicides, preservatives, release agents, adhesive removers, sealers, curing compounds or other incompatible treatments.